



504-362-0781 or 800-889-0781
2236 Manhattan Blvd. Harvey, LA 70058 Fax: 504-367-4216

Sisal, Sash Cord and Hand Fids

Caution: Tensile Strength should never be exceeded. They are obtained from tests on new and unused rope under ideal conditions with standard test methods by the Cordage Institute. They are listed below for general guidelines only.

Gator Supply Co. has more than 1 million pounds of rope in our inventory, one of the largest distributors in the entire United States.



Size (Dia. In.)	Size (Cir. In.)	Tensile Strength In Pounds (Sisal)	Pounds per 100 Feet (Sisal)
Size (Dia. In.)	Size (Cir. In.)	Tensile Strength In Pounds (Sisal)	Pounds per 100 Feet (Sisal)
1/4"	3/4"	430	1.8
5/16"	1"	710	2.6
3/8"	1-1/8"	960	3.8
1/2"	1-1/2"	1,890	7.0
Size No.	Normal Diameter (In.)	Normal Diameter (MM)	Recommended Working Load (LBS)
Size No.	Normal Diameter (In.)	Normal Diameter (MM)	Recommended Working Load (LBS)
8	1/4	6.35	49
10	5/16	7.94	68
12	3/8	9.53	95
16	1/2	12.70	180

Hand Fids

Hand Fids

6" x 1-3/8"

8" x 1-1/2"

10" x 1-1/2"

12" x 1-3/4"

Hand Fids

- 14" x 1-3/4"
 - 16" x 2"
 - 18" x 2"
 - 18" x 3"
 - 20" x 2-1/4"
 - 24" x 3"
-