



504-362-0781 or 800-889-0781

2236 Manhattan Blvd. Harvey, LA 70058 Fax: 504-367-4216

PolyBlend 8-Braid

Our polyblend is premium quality polyester blended with polypropylene identified with two green tracers.

PolyBlend 8-Braid POPULAR APPLICATIONS * Mooring * Towing * Anchor Lines * Slings ADVANCED DURABILITY * Excellent ultra-violet light resistance * Low Elongation * Good abrasion CHARACTERISTICS * Easily Spliced * Firm smooth running flexibility * Balanced construction POLYBLEND 8-BRAID * Fiber - Polyester blended w/polypropylene fiber * Construction - 4X2 * Specific Gravity - 1.20 * Melting Point - 165°/265°F * Elongation at break - 18-20% * Water absorption - 0.1%	Diameter		Circumference		Weight	Breaking Strength
	(INCH)	(MM)	(INCH)	(MM)	(Lbs/100FT)	MIN (Lbs)
	2	48	6	144	78	52,000
	2-1/8	52	6-1/2	156	90.8	61,000
	2-1/4	56	7	168	104	69,000
	2-1/2	60	7-1/2	180	120	80,000
	2-5/8	64	8	192	134	90,000
	3	72	9	216	169	114,000
	3-1/4	80	10	240	206	137,000
	3-1/2	88	11	264	248	162,000
	4	96	12	288	293	190,000
	* Manufactured tested according to ISO and BSEN standards. * Warning: The minimum breaking strength should never be considered as the safe working load of the rope.					