



504-362-0781 or 800-889-0781

2236 Manhattan Blvd. Harvey, LA 70058 Fax: 504-367-4216

HI-GRIP P/D

Gator Supply offers this unique 3-strand rope. Designed especially for hand lines. It features a spun polyester cover over polypropylene. Hi-Grip is a 3-Strand rope with a spun Polyester jacket twisted over a Polypropylene core. This product offers excellent handling characteristics, wet or dry.

POPULAR APPLICATIONS

- * Mooring
- * Towing
- * Anchor Lines

ADVANCED DURABILITY

- * Excellent ultra-violet light resistance.
- * Low Elongation
- * Excellent abrasion for longer working life.

SUPER STRENGTH

- * 45% stronger than standard Combo.
- * A cost effective Super Strength Rope.

SUPER COMBO 3-STRAND

- * Fiber - Superdan and Polyester fiber
- * Construction - Twisted
- * Specific Gravity - 1.20
- * Melting Point - 165°/265°F
- * Elongation at break- 20-22%
- * Water absorption - 0-1%

Dia. (Inch)	Dia. (MM)	Circ. (Inch)	Circ. (MM)	Weight (Lbs/100ft)	Breaking Strength Avg (Lbs)	Breaking Strength Min (Lbs)	Stock Item (600 FT)
Dia. (Inch)	Dia. (MM)	Circ. (Inch)	Circ. (MM)	Weight (Lbs/100ft)	Breaking Strength Avg (Lbs)	Breaking Strength Min (Lbs)	Stock Item (600 FT)
1/4	6	3/4	18	1.4	1,830	1,670	
5/16	8	1	24	2.5	3,480	3,170	
3/8	9	1-1/8	27	3.6	4,320	3,920	
7/16	11	1-1/4	33	5	5,350	4,870	
1/2	12	1-1/2	36	6.4	7,560	6,870	
9/16	14	1-3/4	42	8.2	10,200	9,320	
5/8	16	2	48	10.4	12,700	11,500	
3/4	18	2-1/4	54	14	16,000	14,600	
7/8	22	2-3/4	66	20	23,200	21,100	
1	24	3	72	24.3	26,700	24,300	
1-1/16	26	3-1/4	78	27.5	30,900	28,100	
1-1/8	28	3-1/2	84	32	34,700	31,600	
1-1/4	30	3-3/4	90	37	38,100	34,600	
1-5/16	32	4	96	42	43,500	39,600	
1-1/2	36	4-1/2	108	56	53,300	48,500	
1-5/8	40	5	120	65.6	64,300	58,500	
1-3/4	44	5-1/2	132	78.3	77,000	70,000	
2	48	6	144	98.4	96,500	87,800	600
2-1/8	52	6-1/2	156	112.1	105,000	95,500	

Dia. (Inch)	Dia. (MM)	Circ. (Inch)	Circ. (MM)	Weight (Lbs/100ft)	Breaking Strength Avg (Lbs)	Breaking Strength Min (Lbs)	Stock Item (600 FT)
2-1/4	56	7	168	133.7	123,900	112,700	
2-1/2	60	7-1/2	180	149.6	141,500	128,700	
2-5/8	64	8	192	168.5	150,600	145,000	600
3	72	9	216	212	203,700	185,200	
3-1/4	80	10	240	260.7	243,000	221,000	