



504-362-0781 or 800-889-0781

2236 Manhattan Blvd. Harvey, LA 70058 Fax: 504-367-4216

Polypropylene 8-Braid

Our 8-braid polypro is offered in yellow and black.

Gator's 8-Braid Polypro is made with Dan Line jacket and a twisted split film core.

POPULAR APPLICATIONS * General Applications * Mooring Lines * Float Lines * Tag Lines ADVANCED DURABILITY * Good U-V light resistance * Moderate Elongation * Good abrasion * Floats CHARACTERISTICS * Easily Spliced * Light Weight * Balanced Construction POLYPRO 8-BRAID * Fiber - Polypropylene * Construction - 4 X 2 * Specific Gravity - 0.91 * Melting Point - 250°F * Elongation at break - 18-20% * Water absorption - none	Dia.	Dia.	Circ.	Circ.	Weight	Breaking Strength
	(Inch)	(MM)	(Inch)	(MM)	(Lbs/100ft)	Min (Lbs)
	1-1/2	36	4-1/2	108	38.5	29,700
	1-5/8	40	5	120	47.5	36,000
	1-3/4	44	5-1/2	132	57	43,000
	2	48	6	144	69	52,000
	2-1/4	56	7	168	92	69,000
	2-1/2	60	7-1/2	180	107	80,000
	2-5/8	64	8	192	120	90,000
	3	72	9	216	153	114,000
	3-1/4	80	10	240	190	137,000
	4	96	12	288	275	19,000
	**** 4-1/4				325.0	
	**** 4-1/2				375.0	
	**** 5				430.0	
	**** 5-1/4				490.0	
	**** 5-5/8				555.0	
	**** 6				625.0	
**** Denotes Factory Order						

