



504-362-0781 or 800-889-0781

2236 Manhattan Blvd. Harvey, LA 70058 Fax: 504-367-4216

---

## **Polypropylene 3-Strand**

### **Polypropylene 3-Strand Rope**

Our polypro is offered in yellow or black from 3/16 to 1" in dia.

Black/black/yellow from 1-1/4" and above in dia.

Sizes 3/16" thru 1" is a split film construction

Gator's Polypro is a regular lay 3-strand rope. It is the traditional very economical yellow polypro. It has low stretch and good abrasion.

POPULAR APPLICATIONS * General Applications * Mooring Lines * Float Lines * Hand Lines * Pulling Ropes ADVANCED DURABILITY * Good U-V light resistance * Moderate Elongation * Good abrasion * Floats CHARACTERISTICS * Good Knot Retention * Good Dielectric Properties * Light Weight * Balanced Construction POLYPRO 3-STRAND * Fiber - Polypropylene * Contruction - Twisted * Specific Gravity - 0.91 * Melting Point - 250°F * Elongation at break - 20-22% * Water absorption - none	Diameter		Circumference		Weight	Breaking Strength
	(Inch)	(MM)	(Inch)	(MM)	(Lbs/100Ft)	Avg (Lbs)
	3/16	5	9/16	15	0.7	800
	1/4	6	3/4	18	1.2	1,250
	5/16	8	1	24	1.8	1,900
	3/8	9	1-1/8	27	2.8	2,700
	7/16	11	1-1/4	33	3.8	3,500
	1/2	12	1-1/2	36	4.7	4,200
	5/8	16	2	48	7.5	6,200
	3/4	18	2-1/4	54	10.7	8,500
	7/8	22	2-3/4	66	15	11,500
	1	24	3	72	18	14,000
	1-1/8	28	4-1/2	84	23.7	18,300
	1-1/4	30	3-3/4	90	27	21,000
	1-1/2	36	4-1/2	108	38.5	29,700
	1-5/8	40	5	120	47.5	36,000
	1-3/4	44	5-1/2	132	57	43,000
	2	48	6	144	69	52,000
	2-1/4	56	7	168	92	69,000
	2-1/2	60	7-1/2	180	107	80,000
	2-5/8	64	8	192	120	90,000
	3	72	9	216	153	114,000
	3-1/4	80	10	240	190	137,000
	3-5/8	88	11	264	232	162,000
	4	96	12	288	275	190,000