



504-362-0781 or 800-889-0781

2236 Manhattan Blvd. Harvey, LA 70058 Fax: 504-367-4216

Lock Line 3-Strand

Our Lock Line is designed with a high holding spun polyester. The spun and filament polyester blend in the cover yarns gives a unique handling line with superior abrasion resistance. This construction brings together the highest strength-to-weight ratio; lowest elongation; with excellent handling qualities available for Towboat and Barge work. Manufactured from spun polyester cover yarns for greater abrasion and frictional heat resistance.

Gator's 3-Strand Lock Line has the special polyolefin core to help keep the line round and firm.

POPULAR APPLICATIONS

- * Barge and Dredge
- * Working Line
- * Lock Lines

ADVANCED DURABILITY

- * Excellent ultra-violet light resistance.
- * Excellent abrasion for longer working life.
- * Low Elongation
- * Excellent Hand and Rendering Properties.
- * Medium/Firm Lay.

SPECIAL BENEFITS

- * Same day shipment in most cases, to anywhere.

LOCK LINE 3-STRAND

- * Fiber - Spun and Filament Polyester fiber-Polyolefin
- * Construction - Twisted
- * Specific Gravity - 1.14
- * Melting Point - 480°F
- * Elongation at 30% of Tensile - 4%
- * Water absorption - 0-1%

Dia. (Inch)	Dia. (mm)	Circ. (Inch)	Circ. (mm)	Weight (Lbs/100ft)	Breaking Strength (Avg - lbs)	Breaking Strength (Min - lbs)	Stock Item (300/600ft)
Dia. (Inch)	Dia. (mm)	Circ. (Inch)	Circ. (mm)	Weight (Lbs/100ft)	Breaking Strength (Avg - lbs)	Breaking Strength (Min - lbs)	Stock Item (300/600ft)
1 1/2"	36	4 1/2"	108	47	43,000	39,000	600
1 5/8"	40	5"	120	48.67			
1 3/4"	44	5 1/2"	132	62			
2"	48	6"	144	81	71,000	64,000	300/600
2 1/4"	56	7"	168	100			
2 1/2"		7 1/2"		116			
2 5/8"		8"		133	99,000	90,000	600
3"		9"		160			

