



504-362-0781 or 800-889-0781

2236 Manhattan Blvd. Harvey, LA 70058 Fax: 504-367-4216

Super Dan Orange 3-Strand

Introducing our highly visible international safety orange with 2 green tracers. Super dan rope cuts down on the "slips, trips, and falls". Because Superdan rope is manufactured from high tenacity polypropylene yarns, Superdan offers easy handling, high strength and excellent abrasion resistance.

Superdan Rope



Advanced Durability

- Excellent anti-abrasion properties contribute to longer working life. (over 10% compared to standard Ropes)

- High ultra-violet light resistance.

Super Strength

- 50% better breaking strength compared to BS and ISO standards and specifications.
- A cost effective super strength rope.

Variety of Applications

- A multi purpose rope ideal for general industrial & commercial fishing applications.
- An excellent rope for deep sea pot rope.



The fiber construction of DSR Corp Superdan rope.



The fiber construction of general Polypropylene rope.

- Manufactured tested according to ISO and BSEN standards.

- **Warning: The minimum breaking strength should never be considered as the safe working load of the rope.**

Diameter		Circumference		Weight	Breaking Strength	
INCH	MM	INCH	MM	LBS/100FT	AVG(LBS)	MIN(LBS)
3/16	5	9/16	15	0.73	1,100	1,000
1/4	6	3/4	18	1.23	1,830	1,670
5/16	8	1	24	2.22	3,480	3,170
3/8	9	1-1/8	27	2.80	4,320	3,920
7/16	11	1-1/4	33	3.33	5,350	4,870
1/2	12	1-1/2	36	4.88	7,560	6,870
9/16	14	1-3/4	42	6.65	10,200	9,320
5/8	16	2	48	8.50	12,700	11,500
3/4	18	2-1/4	54	10.90	16,000	14,600
13/16	20	2-1/2	60	13.30	19,300	17,600
7/8	22	2-3/4	66	16.30	23,200	21,100
1	24	3	72	19.20	26,700	24,300
1-1/16	26	3-1/4	78	22.50	30,900	28,100
1-1/8	28	3-1/2	84	26.20	34,700	31,600
1-1/4	30	3-3/4	90	29.60	38,100	34,600
1-5/16	32	4	96	34.00	43,500	39,600
1-1/2	36	4-1/2	108	43.30	53,300	48,500
1-5/8	40	5	120	53.20	64,300	58,500
1-3/4	44	5-1/2	132	65.10	77,000	70,000
2	48	6	144	83.40	96,500	87,800
2-1/8	52	6-1/2	156	93.70	105,000	95,500
2-1/4	56	7	168	112.70	123,900	112,700
2-1/2	60	7-1/2	180	128.60	141,500	128,700
2-5/8	64	8	192	145.40	159,600	145,000
2-3/4	68	8-1/2	204	173.00	187,700	170,700
3	72	9	216	187.70	203,700	185,200
3-1/4	80	10	240	225.20	243,000	221,000
3-1/2	84	10-1/2	252	259.40	279,700	254,400
3-5/8	88	11	264	283.50	305,700	278,000
4	96	12	288	334.90	361,200	328,500
