

504-362-0781 or 800-889-0781 2236 Manhattan Blvd. Harvey, LA 70058 Fax: 504-367-4216

Wire Rope Towing Lines

Large inventory of various sizes in 6x26 and 6x36 Classes, ABS approved, with C Lube, on steel reels with close spelter socket on inside. All are ready for immediate shipment.

Gator Supply has a sizeable part of the wire rope inventory dedicated for towing line applications. We recognize the importance of this product to our customers and have made the investment to have a large amount of sizes readily available.

All of the Tow Lines on this web page (1-1/4"thru 2-1/2") are ABS approved, with C Lube, on steel reels with close spelter socket on inside and ready for immediate shipment

Diameter/Length

Diameter/Length
Diameter/Length
1-1/4" X 1200 Ft.
1-1/4" X 1400 Ft.
1-1/4" X 1600 Ft.
1-1/4" X 1800 Ft.
1-1/2" X 1800 Ft.
1-1/2" X 2000 Ft.
-
IWRC (Independent Wire Rope Core) XIP (extra improved plow steel) with Close Spelter on inside and ABS approved.
Diameter/Length
Diameter/Length
1-3/4" X 1800 Ft.
1-3/4" X 2000 Ft.
1-3/4" X 2100 Ft.
1-3/4" X 2200 Ft.
-
2" X 2000 Ft.
2" X 2200 Ft.
2" X 2400 Ft.
2" X 2500 Ft.
2" X 2800 Ft.
2" X 3000 Ft.
2-1/4" X 2000 Ft.
2-1/4" X 2200 Ft.
2-1/4" X 2400 Ft.
2-1/4" X 2500 Ft.
2-1/4" X 2800 Ft.
2-1/4" X 3000 Ft.
2-1/2" X 2500 Ft.
2-1/2" X 3000 Ft.
IWRC (Independent Wire Rope Core) XIP (extra improved plow steel) with Close Spelter on inside and ABS approved.

IWRC (Independent Wire Rope Core) XIP (extra improved plow steel) with Close Spelter on inside and ABS approved.