

504-362-0781 or 800-889-0781 2236 Manhattan Blvd. Harvey, LA 70058 Fax: 504-367-4216

7x19 Stainless Steel Cable



7 x 19



7 x 19

*Listed for comparison only. Actual operating loads may vary, but should never exceed recommended design factor or 20% of catalog Breaking Strength.

Meeting dimensional and strength requirements of MIL-W-83420E.

Size	Approx. Wt. per 1	000 Ft. in Pounds	Breaking Strengt	h in Pounds*
Size	Approx. Wt. per 100	0 Ft. in Pounds	Breaking Strength	in Pounds*
3/32" *>	⁴ 17		920	
1/8" **	29		1,760	
5/32" *	⁴⁵		2,400	
3/16" *	⁴ 65		3,700	
7/32" *	⁴ 86		5,000	
1/4" **	110		6,400	
5/16" *	[°] 173		9,000	
3/8" **	243		12,000	

Size	Approx. Wt. per 1000 Ft. in Pounds	Breaking Strength in Pounds*
Size	Approx. Wt. per 1000 Ft. in Pounds	Breaking Strength in Pounds*
1/16" (7x7)	7.5	480
1/8"	29	1,670
3/16"	65	3,565
1/4"	110	5,875
5/16"	173	8,825
3/8"	243	11,760

^{**} According to Federal Specifications RR-W-410D.