



504-362-0781 or 800-889-0781
2236 Manhattan Blvd. Harvey, LA 70058 Fax: 504-367-4216

Proof Coil Chain Grade 30

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT OF CHAIN. NEVER USE PROOF COIL CHAIN FOR OVERHEAD LIFTING OR WHERE ITS FAILURE WILL CAUSE DAMAGE TO PROPERTY OR LIFE. Read important warnings and information when using chain on web page

PROOF COIL CHAIN (GRADE 30)

Bright, zinc plated or hot galvanized. According to ASTM A413 and NACM Specification. Proof tested to 2x the Working Load Limit.

Nominal Size Inches	Nominal Size mm	Working Load Limit in Pounds	Feet per Drum	Feet per 1/2 Drum	Minimum Weight per Foot	Max. Length per 100 Links
Nominal Size Inches	Nominal Size mm	Working Load Limit in Pounds	Feet per Drum	Feet per 1/2 Drum	Minimum Weight per Foot	Max. Length per 100 Links
1/8"	4.0	400	----	1,000	.17	90.5"
3/16"	5.5	800	1600	800	.33	96.4"
1/4"	7.0	1,300	800	400	.63	124.0"
5/16"	8.0	1,900	550	275	.93	129.1"
3/8"	10.0	2,650	400	200	1.41	137.8"
1/2"	13.0	4,500	200	100	2.40	179.1"
5/8"	16.0	6,900	150	75	3.58	220.5"
3/4"	20.0	10,600	100	50	5.48	275.6"
7/8"	22.0	12,800	80	40	7.31	258.7"
1"	26.0	17,900	60	30	9.41	287.8"