




504-362-0781 or 800-889-0781
 2236 Manhattan Blvd. Harvey, LA 70058 Fax: 504-367-4216

Eye & Eye Swivels

DROP FORGED SWIVELS

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT. Swivels are not intended to rotate under load.

Eye & Eye Swivels: Meets or exceeds the performance requirements of Federal Specification RR-C-271D. Hot galvanized.



Size (A)	Work Load Limit LBS.	Approx. Wt. ea. LBS.	Ins. B	Ins. C	Ins. E	Ins. F
1/4"	850	.2	.69	.75	.94	2.88
5/16"	1,250	.38	.75	1.00	1.13	3.63
3/8"	2,250	.68	.94	1.25	1.38	4.25
1/2"	3,600	1.4	1.38	1.50	1.94	5.63
5/8"	5,200	2.5	1.63	1.75	2.31	6.63
3/4"	7,200	3.8	1.81	2.00	2.56	7.25
7/8"	10,000	6.0	2.06	2.25	3.02	8.28
1"	12,500	8.5	2.35	2.48	3.43	9.53
1.1/4"	18,000	16.3	2.69	3.13	3.69	11.13
1.1/2"	45,200	46.0	4.18	4.00	4.18	17.12