



504-362-0781 or 800-889-0781

2236 Manhattan Blvd. Harvey, LA 70058 Fax: 504-367-4216

Galvanized Wire Rope Thimbles

WIRE ROPE THIMBLES

Galvanized Wire Rope Thimbles Hot galvanized, according to Federal Specification FF-T-276b, Type III	Size in Inches	Approx. Weight Each in Pounds	Dimensions in Inches				
			A	B	C	D	E
	1/4	0.075	2.19	1.50	1.63	0.88	0.41
	5/16	0.140	2.50	1.81	1.88	1.06	0.50
	3/8	0.250	2.88	2.13	2.13	1.13	0.66
	7/16	0.360	3.25	2.25	2.38	1.25	0.75
	1/2-9/16	0.510	3.63	2.56	2.75	1.50	0.84
	5/8	0.750	4.25	3.00	3.25	1.75	1.00
	3/4	1.470	5.00	3.50	3.75	2.00	1.25
	7/8	1.850	5.50	4.00	4.25	2.25	1.38
	1	3.000	6.13	4.38	4.50	2.50	1.56
	1.1/8 - 1.1/4	3.800	7.00	5.63	5.13	2.88	1.88
	1.1/4 - 1.3/8	8.600	9.06	6.75	6.50	3.50	2.25
	1.3/8 - 1.1/2	11.000	9.06	7.00	6.50	3.50	2.63
	1.5/8	11.800	11.25	8.13	8.00	4.00	2.72
	1.3/4	17.900	12.19	8.25	9.00	4.50	2.88
	1.7/8 - 2	25.000	15.13	10.25	12.00	6.00	3.13
	2.1/4	45.000	17.13	11.88	14.00	7.00	3.63
2.1/2*	63.500	22.25	12.75	17.50	8.00	4.38	

*2.1/2" available with or without gusset plates.

Hot dip galvanized. Meets the performance requirements of Federal Specification FF-T-276, current revision, Type III



WARNING: NEVER EXCEED WORKING LOAD LIMIT
